

Peek 625X Plus Vehicle Detector

Peek Traffic Corporation

The Peek 625X Plus vehicle detector detects when vehicles are present and monitors inductive loops of practically all dimensions. It can detect both parked and moving vehicles and control access.



Description

The Peek 625X Plus provides a host of settings that are adjustable using front panel DIP switches. Sensitivity is adjusted using a 10-setting rotary dial.

The user can set a 2-second detection delay to ignore fast moving vehicles or extend the detection time by 2, 5 or 10 seconds to ensure detection of slow moving vehicles.

The detection monitor reports two types of loop faults: open loop and shorted loop. Each fault type is indicated by a specific flashing sequence of the power indicator or, if so programmed, relay 2 emits an output signal.

The Peek 625X Plus detector is equipped with two separate programmable relay outputs:

- Relay 1:
 - Main detection output
 - Factory set to be fail safe in the case of power interruptions
 - Can be modified by delay and extension
 - Fail safe mode easily changeable
- Relay 2 - Can be set to one of the following:
 - True presence (no delay or extension)
 - Pulse on vehicle entering the loop
 - Pulse on vehicle exiting the loop
 - Loop fail output

A non-volatile memory prevents the loss of vehicle signals following a voltage drop of 3 seconds or less (the 625X “remembers” the vehicle).

Specifications

Standard functions

- Automatic tuning to the loop frequency
- Inherent noise filtering algorithms allowing reliable operation in any electrical situation
- Protection from damage if plugged into the wrong voltage
- Fail safe and fail secure configurations in case of power interruptions
- Sensitivity boost feature
- Onsite selectable fail safe and fail secure configurations in case of power interruptions
- Ongoing compensation for the impacts of weather conditions
- 11-pin Amphenol male connector

Technical characteristics

- Supply voltage:
- 10-30 VAC or VDC (LV model)
- 117 VAC (117 model)
- 230 VAC (230 model)
- Consumption: less than 3 W
- Inductance range: 20-1000 μ H
- Operating temperature range: -34 to +74°C (-29 to +165°F)
- Dimensions: 60 mm (high) x 45 mm (wide) x 92 mm (deep) (2.375 x 1.75 x 3.61")

Models

- 625X Plus-LV: 10-30 VAC or VDC supply voltage
- 625X Plus-117: 117 VAC supply voltage
- 625X Plus-230: 230 VAC supply voltage

For more information: 1 800 363-5913

Created on 17.05.2025 at 16:44:38 EDT