

## LED Blank Out Sign - No Right turn

### Orange Traffic

Orange Traffic's intermittent road signs are designed to clearly indicate authorized vehicle manoeuvres at intersections and on roadways. Here, the sign is used to remind road users that right turns are forbidden. The sign is lit according to conditions and times to quickly indicate to road users if they are allowed to turn or not and thus avoid the confusion that can stem from indicating when turns are forbidden on the same sign or a separate sign.



### Description

These signs are the most readable on the market because they are built with high-quality components such as LEDs specially designed for road traffic and a unique constant current modular power system that eliminates flickering.

Orange Traffic's blank out signs also enable energy cost savings because they consume up to 90% less electricity than conventional fibre optic signs. Furthermore, their components are designed to facilitate installation, maintenance and upgrading and therefore lower operating costs. Finally, it is also possible to reuse the enclosure and wiring and replace only the front (LED) panel.

The wiring may be installed in the panel itself or consolidated with other power supplies in a more accessible area to minimize traffic disturbances during maintenance operations.

Orange Traffic offers an array of standard LED panels and several messages can be combined in a single panel. However, thanks to their modular design, these panels are easily adaptable to your requirements, and Orange Traffic is also able to design special or oversized panels. Feel free to tell us about your specific needs.

### Specifications

#### FUNCTIONAL CHARACTERISTICS

- Independently powered and controlled messages. The power modules are compatible with all Orange Traffic LED display panels and can be replaced while powered
- The front panel assembly, as well as the main components, can be replaced using just a flat screwdriver, which facilitates upgrading and maintenance operations
- Fully compatible with:
  - Standard traffic signal conflict monitors (NEMA and 170)
  - Orange Traffic's SPC-22 programmable clock, allowing for the panel's autonomous operation according to pre-established schedules
  - Earlier versions of Orange Traffic blank out signs (backward compatibility)
- Dry contact for the confirmation or display control alarm of each message and for interlocking two contiguous messages without additional material
- 8-mm (3/16") thick UV-resistant front lens for longer LED life

## **TECHNICAL CHARACTERISTICS**

- Waterproof aluminium enclosure that meets NEMA requirements for type 4 enclosures
- Compliance with Institute of Transportation Engineers (ITE) requirements applying to LED road signs
- Exterior dimensions:
  - 710 x 710 mm (28 x 28") for 600-mm (24") messages
  - 710 x 965 mm (28 x 38") for 750-mm (30") messages
- Depth: 200 mm (8")
- Supply voltage: 90-135 VAC/60 Hz
- Maximum power: 30 W; nominal power: 15 W
- Power factor > 90%
- Compliance with operating temperature criteria of NEMA TS2 standard (-34 to +74°C (-30 to +165°F))
- LEDs of stable brightness and chromaticity over the entire power and temperature ranges

## **OPTIONAL ACCESSORY**

- 300-mm (12") deep visor for improved visibility of flashing lights in direct sunlight

---

**For more information: 1 800 363-5913**

Created on 21.01.2026 at 11:12:05 EST