

## Superposed Pedestrian Signals

### Orange Traffic

Orange Traffic proposes LED signals comprising two superposed display modules: one module represents a main or silhouette, depending on the situation, whereas the second is a 12-second countdown module.



### Description

These signals provide increased visibility and eliminate the risks of signal misinterpretation. Pedestrians thus benefit from increased safety when crossing intersections.

### Specifications

#### Functional characteristics

- Uniformity that complies with ITE's PTSCI uniformity standard regarding minimum and maximum brightnesses
- Full pre-emption compatibility
- Compliance with the MUTCD countdown standard
- Separate and dedicated power supplies for increased safety and reliability
- Intertek/ETL certification and registration with ETL's certification program

#### Protection

- Anticapillary wiring that prevents water infiltration
- Power supplies covered by a damp-proof coating
- Fuse providing an increased level of protection against line and charge surge
- Protection against transient voltage surges that exceeds NEMA and ITE standards

#### Technical characteristics

- Dimensions: 30.5 x 30.5 cm (12 x 12 in.)
- Power supply: 80-135 VAC, 60 ± 3 Hz
- Power consumption (at 25°C):
  - Main: 8 W
  - Silhouette: 6 W

- Countdown: 5 W
- Maximum brightness:
  - Main: 1400 cd/m<sup>2</sup>
  - Silhouette: 2200 cd/m<sup>2</sup>
  - Countdown: 1400 cd/m<sup>2</sup>

---

**For more information: 1 800 363-5913**

Created on 05.03.2026 at 07:51:25 EST